

# DUMMY LOADS AND ATTENUATORS

## ATTENUATORS

1 W  
0-1 GHz



### DESCRIPTION:

- ★ This 1 W series include 3 dB, 10 dB, 20 dB and 30 dB attenuators.
- ★ This series of attenuators have very low SWR and are especially suitable for use with:
  - Coaxial Transmission Lines.
  - Power Monitors.
  - Wattmeters.



PRO-ATT...-1-1-N



PRO-ATT...-1-1-BNC

### SPECIFICATIONS:

	ELECTRICAL	
	PRO-ATT...-1-1-N	PRO-ATT...-1-1-BNC
FREQUENCY RANGE	0-1 GHz	0-1 GHz
MAX. INPUT POWER	1 W	1 W
ATTENUATION	3, 10, 20 or 30 dB Other attenuation values on request	3, 10, 20 or 30 dB Other attenuation values on request
VAR. on ATTENUATION	± 0.5 dB	± 0.5 dB
IMPEDANCE	Nom. 50 Ω	Nom. 50 Ω
SWR	≤ 1.25	≤ 1.25
MECHANICAL		
TEMP. RANGE	-30° C i +60° C	-30° C i +60° C
CONNECTORS	N-female – N-male	BNC-female – BNC-female
DIMENSIONS	ø21 x 69 mm	ø19.5 x 66 mm
WEIGHT	Approx. 80 g	Approx. 30 g

PROCOM A/S reserve the right to amend specifications without prior notice.