

CXL 1800-6LW

6 dBd Omnidirectional Marine and Base Station Antenna for the 1800 MHz Band




DESCRIPTION:

- ★ Vertically polarised, omnidirectional marine and base station antenna.
- ★ Approximately 6 dBd gain.
- ★ Provided with the sturdy "LW" mast mount – a lightweight, multipurpose, epoxy-coated mounting bracket made of non-corrosive aluminium.
- ★ The accompanying U-bolts and fittings are made of stainless steel.
- ★ To be mounted on vertical or horizontal mast tubes, 16 to 54 mm in outer diameter.
- ★ The cable can be led either on the outside or along the inside of the mast tube.
- ★ Large bandwidth with respect to both SWR and gain.
- ★ Highly suitable for duplex operation with large spacing between the TX and the RX frequencies, e.g. the DCS-1800/PCN cellular system.
- ★ The antenna element is sealed in a high-quality, conical glassfiber tube.
- ★ All metal parts in the antenna are DC-grounded to reduce the noise caused by atmospherical discharge. Consequently, the antenna shows a DC-short across the coaxial cable.
- ★ The CXL 1800-6LW is a vibration-proof, lightweight, slim-line, corrosion resistant, modern style marine and base station antenna.



SPECIFICATIONS:

ELECTRICAL	
MODEL	CXL 1800-6LW
ANTENNA TYPE	Coaxial, colinear antenna, broad-banded
FREQUENCY	1700–1900 MHz
IMPEDANCE	Nom. 50 Ω
POLARISATION	Vertical
GAIN	8 dBi (6 dBd)
BANDWIDTH	≥ 200 MHz at SWR ≤ 1.75
SWR	≤ 1.75, typ. ≤ 1.5
MAX. POWER	100 watt
ANTISTATIC PROTECTION	All metal parts DC-grounded (Connector shows a DC-short)
MECHANICAL	
TEMP. RANGE	-30° C → +70° C
CONNECTOR	N-female
WIND SURFACE	Approx. 0.04 m ²
WIND LOAD	Approx. 44 N (at 150 km/h)
COLOUR	Marine white
MATERIALS	Shroud: Polyurethane coated glassfiber Mounting bracket: Seawater resistant aluminium, epoxy-coated Clamps: Stainless steel
TOTAL HEIGHT	Approx. 1.2 m
DIA. IN TOP END	21 mm
DIA. IN BOTTOM END	23 mm
WEIGHT	Approx. 900 g
MOUNTING	On 16–54 mm dia. mast tube

MULTI-PURPOSE MOUNTING BRACKET:



- ① Mast tube D_1 , min. = 30 mm
Mast tube D_0 , max. = 54 mm
- ② Mast tube D_0 , max. = 54 mm
Mast tube D_0 , min. = 16 mm
- ③ Mast tube D_0 , max. = 54 mm
Mast tube D_0 , min. = 16 mm



PLEASE NOTE:

The antenna is delivered with a DC-connection between the antenna element and the mounting bracket.


PROCOM A/S reserve the right to amend specifications without prior notice.

CXL 1800-6LW

6 dBd Omnidirectional Marine and Base Station
Antenna for the 1800 MHz Band



TYPICAL RADIATION PATTERN (E-PLANE)



TYPICAL RADIATION PATTERN (H-PLANE)

