

# FSP 70 1/4/...-IC-F61

*"StraightFlex" Antenna for ICOM Portable Equipment in the 70 cm Band*

PROCOM

## DESCRIPTION:

- ★ Highly flexible, polyethylene covered StraightFlex steel wire.
- ★ Full-size  $1/4 \lambda$  whip.
- ★ Highest quality materials in an elegant design.
- ★ Delivered factory tuned and tested to ensure minimum SWR.
- ★ Especially designed for ICOM IC-F61 (450 MHz band).

## ORDERING DESIGNATIONS:

FREQUENCY	380–430 MHz	400–450 MHz	420–470 MHz
TYPE NO.	FSP 70 1/4/s-IC-F61	FSP 70 1/4/l-IC-F61	FSP 70 1/4/h-IC-F61

## SPECIFICATIONS:

ELECTRICAL	
MODEL	FSP 70 1/4/...-IC-F61
ANTENNA TYPE	$1/4 \lambda$ antenna for portable equipment
FREQUENCY	70 cm band covered by three models
IMPEDANCE	Nom. 50 $\Omega$
POLARISATION	Vertical
GAIN	0 dB (equal to a $1/4 \lambda$ portable antenna)
BANDWIDTH	$\geq 50$ MHz @ SWR $\leq 2.0$
SWR	$< 2$ when mounted directly on portable equipment
MAX. POWER	100 watt
MECHANICAL	
MATERIALS	Polyethylene covered flexible steel wire Environment-proof plastics Black-chromed brass
COLOUR	Black
TOTAL HEIGHT	Approx. 200 mm (dep. on type)
WEIGHT	Approx. 15 g
CONNECTOR	SMA (male) special for IC-F61

TETRA

