

RG 174 FME-CABLES



ORDERING CODE NO.

FME-RG 174/U-PROCOM

1 m FME RG 174




1 m RG 174 coaxial cable with FME-connector mounted at both ends

2 m FME RG 174



2 m RG 174 coaxial cable with FME-connector mounted at both ends

3 m FME RG 174



3 m RG 174 coaxial cable with FME-connector mounted at both ends

4 m FME RG 174



4 m RG 174 coaxial cable with FME-connector mounted at both ends

5 m FME RG 174



5 m RG 174 coaxial cable with FME-connector mounted at both ends

6 m FME RG 174



6 m RG 174 coaxial cable with FME-connector mounted at both ends

ORDERING CODE NO.

FME-EFME RG 174/U-PROCOM

**1 m FME-EFME
RG 174**



1 m RG 174 coaxial cable with FME-connector mounted at one end and EFME-connector at the other end

**2 m FME-EFME
RG 174**



2 m RG 174 coaxial cable with FME-connector mounted at one end and EFME-connector at the other end

**3 m FME-EFME
RG 174**



3 m RG 174 coaxial cable with FME-connector mounted at one end and EFME-connector at the other end

**4 m FME-EFME
RG 174**



4 m RG 174 coaxial cable with FME-connector mounted at one end and EFME-connector at the other end

**5 m FME-EFME
RG 174**



5 m RG 174 coaxial cable with FME-connector mounted at one end and EFME-connector at the other end

**6 m FME-EFME
RG 174**



6 m RG 174 coaxial cable with FME-connector mounted at one end and EFME-connector at the other end

ORDERING CODE NO.

FME RG 174/U-PROCOM with alternative connectors

**5 m FME-SMB
RG 174**



5 m RG 174 coaxial cable with FME-connector mounted at one end and SMB female-connector at the other end*

**5 m FME-HIROSE
RG 174**



5 m RG 174 coaxial cable with FME-connector mounted at one end and HIROSE male-connector at the other end**

**5 m FME-MCX
RG 174**



5 m RG 174 coaxial cable with FME-connector mounted at one end and MCX male-connector at the other end***

**5 m FME-MFME
RG 174**



5 m RG 174 coaxial cable with FME-connector mounted at one end and MFME male-connector at the other end

* Spec. for: Philips CARIN/VDO Dayton
Blaupunkt RGS 06/08 5"
Peiker

** Spec. for: Alpine
Grundig
Magneti Marelli

*** Spec. for: Aplicom

The applied RG 174 FME coaxial cables are special PROCOM-designs having a low loss for RG 174 standard coaxial cable (below 0.9 dB per m at 900 MHz) and a very precise 50 Ω characteristic impedance. The cables are produced under continuous automatic control to ensure the high quality.

In the design of the FME-connectors the SWR has been minimized ensuring low mismatch loss and maximum power transfer.